TECHNICAL SPECIFICATIONS

Principle Ion selective Electrode (ISE)

Serum, Plasma, Whole Blood, Urine, CSF **Sample Types**

Parameters Na+, K+, Cl-, Ca++, Li+& pH

 $\leq 90 \mu L$ Sample volume

Analysis Time \leq 60 secs

< 60 samples per hour **Throughput**

Calibration Automatic Calibration:

• Two Point Calibration after 4 hrs or just before Sample analysis

• One Point Calibration with each sample analysis

Normal Ranges User defined Normal Ranges for all Sample types with flagging for Abnormal Samples

Data Management Calibration History, Sample History and Control History of last 30 days

Quality Control Tri-Level Quality Control, with L J Plots of last 30 days

Display 5" color LCD with Touchscreen Display, Resolution: 480 x 272 pixels

Printer Built-in 2" (48 mm) Thermal Printer, 42 characters wide

External Interface USB (Keyboard, Barcode, Pendrive)

Operating Temp. 15 to 35°C


Relative Humidity 5 to 85% non-condensing

Power Supply 100 to 240VAC 50/60 Hz

Dimensions 365mm x 255mm x 375mm

Weight | Sample Storage 6.0 Kg | 100,000

Precision



ISE - Tritrol



* Optional Barcode reader available.

AGD Biomedicals (P) Ltd. Mehta Trade Center, Sir M.V. Road, Andheri East, Mumbai - 400 099 INDIA

+91-22-28257999

E:sales@agdbio.com W:www@agdbio.com

P: +91-22-28231061/66 ISO: 9001:2015 ISO: 13485:2016

 ϵ

*Specifications are subject to change without notice.





ACCURATE | RELIABLE | FRIENDLY INTERFACE



EL-120

ELECTROLYTE ANALYZER

- Na+, K+, Cl-, Ca++, Li+, pH
- Low Sample Volume
- Fast Sample Processing
- Low Cost per Test

www.agdbio.com

Erma EL - 120 is ideal for Medium to High Volume Laboratories and Hospitals. It is user Friendly & Reliable. It also allows measurement of specific ions; Accurately and Precisely. This supports Fast Diagnosis.

MAIN MENU

- Large Graphical Display affords convenience of Operation and Minimizes Errors while Entering Data
- User Friendly Software with Interactive Graphical User Interface
- Shortcut Menu Keys for Easy Operation



ANALYSIS

- Aspiration System: Internal Peristaltic Stepper Motor Pump for Accurate and Precise aspiration of Analytes
- Automatic flushing after aspiration of every sample to eliminate carryover
- Precise & Accurate Result



ELECTRODES

- Electrodes are based on Ion Selective Principle
- Electrodes can be refilled.
- Long life and Assured Stability



CALIBRATION

- Two Point Calibration after 4 hrs/ 8 hrs or 12 hrs.
 Programmable as per user
- One Point Calibration with each Sample Analysis
- Display Status of Calibration with Date and Time for each parameter
- Also Displays the Date and Time of next Calibration to be Performed / Due

RUN QUALITY CONTROL

- Levy Jennings plot of daily and monthly QC data to assess the performance
- Helpful for laboratories incase of Accreditation and Quality Assessment

ISEPak

- Convenient easy to place ISEPak which contains reagents required for all parameters
- Integrated reagent Pack for testing of All Parameters
- In-Built Reagent Inventory Management Software

URINE DILUENT AND DEPROTEINIZER

- **Urine Diluent**: Used for the Dilution of Urine Samples to Quantitatively determine Urine Electrolytes.
- **Deproteinizer**: Used for the Cleaning and Maintenance of Electrolyte Analyzer

Measuring Range

PARAMETER	SERUM /PLASMA BLOOD / AQUEOUS
Na ⁺	40 - 205
K ⁺	1.5 - 15
CI-	50 - 200
Ca ⁺⁺	0.2 - 5.0
Li+	0.1- 6.0
рН	5.0 - 9.0

Control		
ate	: 201	8-11-30 15:
ot No	: 5	
ontrol	: LEV	EL 2
Sample	Type : Aqu	eous
aran	mnol/L	Target
va+	141.3	140 (4.0
K +	4.33	4.25 (0.3
C1-	104.7	105 (4.0
ľa++	1.31	1.25 (0.2





ACCURATE | RELIABLE | FRIENDLY INTERFACE www.agdbio.com